

STRIP
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: July

With process factor valid for finished cold rolled and hardened and tempered strip products
Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

GRADE			ALLOY & ENERGY SURCHARGE PER KG													
Alleima	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD	BRL		
Alloyed non-stainless steels and carbon steels																
20C	1.1274	1095	1870	5,30	0,49	0,41	0,55	80	0,76	3,97	0,45	0,25	0,35	3,11		
20C2			2258	5,65	0,52	0,44	0,59	85	0,81	4,23	0,48	0,27	0,37	3,32		
10C16Mo3V1				16,29	1,49	1,26	1,70	244	2,34	12,21	1,40	0,77	1,06	9,56		
Sanprint XP				15,76	1,44	1,22	1,64	236	2,26	11,81	1,35	0,74	1,03	9,26		

Martensitic stainless chromium steels																
6C27	1.4007	420	2234	9,17	0,84	0,71	0,96	138	1,32	6,88	0,79	0,43	0,60	5,39		
7C27Mo2				15,37	1,41	1,19	1,60	231	2,21	11,52	1,32	0,73	1,00	9,03		
Hiflex				15,37	1,41	1,19	1,60	231	2,21	11,52	1,32	0,73	1,00	9,03		
Freeflex				16,21	1,49	1,25	1,69	243	2,33	12,15	1,39	0,77	1,06	9,52		
10C28MO2				15,52	1,42	1,20	1,62	233	2,23	11,63	1,33	0,73	1,01	9,11		
12C27M				9,40	0,86	0,73	0,98	141	1,35	7,05	0,81	0,44	0,61	5,52		
12C27				9,13	0,84	0,71	0,95	137	1,31	6,84	0,78	0,43	0,59	5,36		
14C28N				9,26	0,85	0,72	0,96	139	1,33	6,94	0,79	0,44	0,60	5,44		
13C26			14141	8,96	0,82	0,69	0,93	134	1,29	6,71	0,77	0,42	0,58	5,26		
Damax				12,25	1,12	0,95	1,28	184	1,76	9,18	1,05	0,58	0,80	7,19		
19C27				9,13	0,84	0,71	0,95	137	1,31	6,84	0,78	0,43	0,59	5,36		

Austenitic stainless steels																
12R11	1.4310	301	2331	21,24	1,95	1,64	2,21	319	3,05	15,92	1,82	1,00	1,38	12,47		
11R51	1.4310	301	2231	25,40	2,33	1,96	2,65	381	3,65	19,04	2,18	1,20	1,65	14,92		
13RM19	EN 1.4369			21,52	1,97	1,66	2,24	323	3,09	16,13	1,85	1,02	1,40	12,64		
3X22R60HV	1,4441	316LVM		49,32	4,52	3,81	5,14	740	7,08	36,97	4,23	2,33	3,21	28,96		
2RK65HV				73,03	6,69	5,64	7,61	1 095	10,48	54,74	6,27	3,45	4,75	42,89		
3X8R65				38,66	3,54	2,99	4,03	580	5,55	28,98	3,32	1,83	2,52	22,70		
3R60F1				47,66	4,37	3,68	4,97	715	6,84	35,72	4,09	2,25	3,10	27,99		

Precipitation hardenable steels																
9RU10	1.4568	631	2388	21,50	1,97	1,66	2,24	323	3,09	16,12	1,84	1,02	1,40	12,63		
NANOFLEX				49,41	4,53	3,82	5,15	741	7,09	37,04	4,24	2,34	3,22	29,02		
1RK95				21,33	1,95	1,65	2,22	320	3,06	15,99	1,83	1,01	1,39	12,52		

Duplex stainless steels (austenitic-ferritic)																
SAF2205	EN 1.4462		2377	39,97	3,66	3,09	4,16	600	5,74	29,96	3,43	1,89	2,60	23,47		
SAF2507	EN 1.4410		2328	46,65	4,28	3,60	4,86	700	6,69	34,97	4,00	2,20	3,04	27,40		
SAF3207HD				45,90	4,21	3,55	4,78	689	6,59	34,41	3,94	2,17	2,99	26,96		

Ferritic stainless chromium steel																
1C429				12,01	1,10	0,93	1,25	180	1,72	9,00	1,03	0,57	0,78	7,05		
1C44Mo20				17,82	1,63	1,38	1,86	267	2,56	13,36	1,53	0,84	1,16	10,46		
0XC34				10,14	0,93	0,78	1,06	152	1,45	7,60	0,87	0,48	0,66	5,95		
1C34				10,08	0,92	0,78	1,05	151	1,45	7,56	0,86	0,48	0,66	5,92		

Nickel-base alloy																
SANICRO75X2	UNS N07750			119,32	10,94	9,22	12,43	1 790	17,12	89,44	10,24	5,64	7,77	70,07		
SAN62TiNb				104,12	9,54	8,04	10,85	1 562	14,94	78,04	8,93	4,92	6,78	61,14		

Energy surcharge per kg included in total surcharge				1,99	0,18	0,15	0,21	30	0,29	1,49	0,17	0,09	0,13	1,17		