

STRIP
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: November

With process factor valid for finished cold rolled and hardened and tempered strip products
Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

GRADE			ALLOY & ENERGY SURCHARGE PER KG											
Alleima	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD	BRL
Alloyed non-stainless steels and carbon steels														
20C	1.1274	1095	1870	4,69	0,43	0,37	0,50	74	0,69	3,55	0,40	0,23	0,31	2,67
20C2			2258	5,08	0,46	0,40	0,54	81	0,75	3,85	0,43	0,25	0,34	2,89
10C16Mo3V1				17,14	1,56	1,36	1,82	272	2,54	12,98	1,45	0,83	1,15	9,75
Sanprint XP				16,55	1,50	1,31	1,76	263	2,45	12,54	1,40	0,80	1,11	9,42

Martensitic stainless chromium steels														
6C27	1.4007	420	2234	9,04	0,82	0,71	0,96	143	1,34	6,85	0,77	0,44	0,61	5,14
7C27Mo2				16,08	1,46	1,27	1,71	255	2,38	12,18	1,36	0,78	1,08	9,15
Hiflex				16,08	1,46	1,27	1,71	255	2,38	12,18	1,36	0,78	1,08	9,15
Freeflex				17,00	1,54	1,34	1,81	270	2,51	12,87	1,44	0,82	1,14	9,67
10C28MO2				16,24	1,47	1,28	1,73	258	2,40	12,30	1,38	0,78	1,09	9,24
12C27M				9,30	0,84	0,74	0,99	148	1,38	7,04	0,79	0,45	0,62	5,29
12C27				8,99	0,82	0,71	0,96	143	1,33	6,81	0,76	0,43	0,60	5,12
14C28N				9,14	0,83	0,72	0,97	145	1,35	6,92	0,77	0,44	0,61	5,20
13C26			14141	8,80	0,80	0,70	0,94	140	1,30	6,66	0,75	0,42	0,59	5,01
Damax				12,54	1,14	0,99	1,33	199	1,85	9,49	1,06	0,60	0,84	7,13
19C27				8,99	0,82	0,71	0,96	143	1,33	6,81	0,76	0,43	0,60	5,12

Austenitic stainless steels														
12R11	1.4310	301	2331	20,95	1,90	1,66	2,23	332	3,10	15,86	1,77	1,01	1,41	11,92
11R51	1.4310	301	2231	25,68	2,33	2,03	2,73	408	3,80	19,45	2,18	1,24	1,72	14,61
13RM19	EN 1.4369			21,28	1,93	1,68	2,26	338	3,15	16,12	1,80	1,03	1,43	12,11
3X22R60HV	1,4441	316LVM		51,15	4,65	4,04	5,44	812	7,57	38,74	4,33	2,47	3,43	29,11
2RK65HV				75,63	6,87	5,98	8,04	1 200	11,19	57,28	6,41	3,65	5,08	43,03
3X8R65				40,05	3,64	3,17	4,26	636	5,93	30,33	3,39	1,93	2,69	22,79
3R60F1				49,38	4,48	3,90	5,25	784	7,31	37,40	4,18	2,38	3,31	28,10

Precipitation hardenable steels														
9RU10	1.4568	631	2388	21,19	1,92	1,68	2,25	336	3,13	16,05	1,80	1,02	1,42	12,06
NANOFLEX				52,44	4,76	4,15	5,58	832	7,76	39,72	4,44	2,53	3,52	29,84
1RK95				20,80	1,89	1,64	2,21	330	3,08	15,75	1,76	1,00	1,40	11,83

Duplex stainless steels (austenitic-ferritic)														
SAF2205	EN 1.4462		2377	42,64	3,87	3,37	4,54	677	6,31	32,30	3,61	2,06	2,86	24,26
SAF2507	EN 1.4410		2328	49,87	4,53	3,94	5,30	792	7,38	37,78	4,23	2,41	3,35	28,38
SAF3207HD				48,98	4,45	3,87	5,21	777	7,25	37,10	4,15	2,36	3,29	27,87

Ferritic stainless chromium steel														
1C429				12,22	1,11	0,97	1,30	194	1,81	9,26	1,04	0,59	0,82	6,96
1C44Mo20				18,83	1,71	1,49	2,00	299	2,79	14,26	1,60	0,91	1,26	10,71
0XC34				10,12	0,92	0,80	1,08	161	1,50	7,67	0,86	0,49	0,68	5,76
1C34				10,06	0,91	0,80	1,07	160	1,49	7,62	0,85	0,49	0,67	5,72

Nickel-base alloy														
SANICRO75X2	UNS N07750			116,55	10,58	9,22	12,40	1 850	17,24	88,28	9,88	5,62	7,82	66,32
SAN62TiNb				101,73	9,24	8,04	10,82	1 615	15,05	77,05	8,62	4,91	6,83	57,88

Energy surcharge per kg included in total surcharge				1,67	0,15	0,13	0,18	26	0,25	1,26	0,14	0,08	0,11	0,95