

STRIP
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: March

With process factor valid for finished cold rolled and hardened and tempered strip products
Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

GRADE			ALLOY & ENERGY SURCHARGE PER KG											
Alleima	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD	BRL
Alloyed non-stainless steels and carbon steels														
20C	1.1274	1095	1870	6,72	0,63	0,55	0,75	117	1,02	5,20	0,58	0,34	0,46	3,94
20C2			2258	7,12	0,67	0,58	0,79	124	1,09	5,51	0,62	0,36	0,49	4,17
10C16Mo3V1				19,07	1,80	1,56	2,12	331	2,90	14,74	1,65	0,96	1,32	11,17
Sanprint XP				18,43	1,74	1,51	2,05	320	2,81	14,25	1,60	0,93	1,27	10,80
17N2W3V1				10,22	0,96	0,84	1,14	177	1,56	7,90	0,89	0,52	0,71	5,99

Martensitic stainless chromium steels														
6C27	1.4007	420	2234	11,20	1,06	0,92	1,25	194	1,71	8,66	0,97	0,57	0,77	6,56
7C27Mo2				18,11	1,71	1,48	2,02	314	2,76	14,00	1,57	0,91	1,25	10,61
Hiflex				18,11	1,71	1,48	2,02	314	2,76	14,00	1,57	0,91	1,25	10,61
Freeflex				19,26	1,81	1,58	2,14	334	2,93	14,88	1,67	0,97	1,33	11,28
10C28MO2				18,28	1,72	1,50	2,03	317	2,78	14,13	1,59	0,92	1,26	10,71
12C27M				11,47	1,08	0,94	1,28	199	1,75	8,86	0,99	0,58	0,79	6,72
12C27				11,15	1,05	0,91	1,24	193	1,70	8,62	0,97	0,56	0,77	6,53
14C28N				11,30	1,06	0,92	1,26	196	1,72	8,73	0,98	0,57	0,78	6,62
13C26			14141	10,95	1,03	0,90	1,22	190	1,67	8,46	0,95	0,55	0,76	6,41
Damax				14,63	1,38	1,20	1,63	254	2,23	11,31	1,27	0,74	1,01	8,57
19C27				11,15	1,05	0,91	1,24	193	1,70	8,62	0,97	0,56	0,77	6,53

Austenitic stainless steels														
12R11	1.4310	301	2331	25,05	2,36	2,05	2,79	435	3,82	19,36	2,17	1,26	1,73	14,67
11R51	1.4310	301	2231	29,69	2,80	2,43	3,31	515	4,52	22,95	2,57	1,50	2,05	17,39
13RM19	EN 1.4369			25,37	2,39	2,08	2,82	440	3,87	19,61	2,20	1,28	1,75	14,86
3X22R60HV	1,4441	316LVM		56,71	5,34	4,64	6,31	984	8,64	43,83	4,92	2,86	3,92	33,21
2RK65HV				83,66	7,88	6,85	9,31	1 451	12,74	64,66	7,26	4,22	5,78	49,00
3X8R65				44,62	4,20	3,65	4,97	774	6,80	34,49	3,87	2,25	3,08	26,13
3R60F1				54,84	5,17	4,49	6,11	951	8,35	42,39	4,76	2,77	3,79	32,12

Precipitation hardenable steels														
9RU10	1.4568	631	2388	25,35	2,39	2,07	2,82	440	3,86	19,59	2,20	1,28	1,75	14,85
NANOFLEX				57,07	5,38	4,67	6,35	990	8,69	44,11	4,95	2,88	3,94	33,43
1RK95				25,14	2,37	2,06	2,80	436	3,83	19,43	2,18	1,27	1,74	14,72

Duplex stainless steels (austenitic-ferritic)														
SAF2205	EN 1.4462		2377	45,92	4,33	3,76	5,11	797	7,00	35,49	3,98	2,32	3,17	26,89
SAF2507	EN 1.4410		2328	53,47	5,04	4,38	5,95	928	8,15	41,33	4,64	2,70	3,69	31,32
SAF3207HD				52,71	4,97	4,31	5,87	914	8,03	40,74	4,57	2,66	3,64	30,87

Ferritic stainless chromium steel														
1C429				14,48	1,36	1,18	1,61	251	2,21	11,19	1,26	0,73	1,00	8,48
1C44Mo20				20,94	1,97	1,71	2,33	363	3,19	16,19	1,82	1,06	1,45	12,27
0XC34				12,32	1,16	1,01	1,37	214	1,88	9,52	1,07	0,62	0,85	7,21
1C34				12,25	1,15	1,00	1,36	212	1,87	9,47	1,06	0,62	0,85	7,17

Nickel-base alloy														
SANICRO75X2	UNS N07750			137,56	12,96	11,26	15,31	2 386	20,96	106,32	11,93	6,95	9,51	80,57
SAN62TiNb				120,12	11,32	9,83	13,37	2 084	18,30	92,84	10,42	6,07	8,30	70,35

Energy surcharge per kg included in total surcharge				3,38	0,32	0,28	0,38	59	0,52	2,62	0,29	0,17	0,23	1,98